

STIHL - 30050007409 - Espada motosierra STIHL 35cm 3/8" Rollomatic P LIGHT 1,3mm

017, 018, 019T, 021, 023, MS162, MS170, MS171, MS172, MS180, MS181, MS182, MS190T, MS192T, MS193, MS193T, MS194, MS194T, MS210, MS211, MS212 con equipo de corte de 3/8"

Espada ligera con dos placas de acero soldadas eléctricamente.

Pulverizado con poliamida y reforzada con fibra de vidrio.

Para la recolección de madera, el corte de madera y el corte de leña.

Exenta de mantenimiento gracias al cojinete cerrado en la estrella de reenvío.

Rieles de guía ligeros y versátiles.

Ficha técnica

Longitud de espada: 35cm / 14"

Versión espada: RL-74-Rollomati cLight-1,3-3/8" P-9

Espesor: 1,3mm/.050"

Tipo de espada: Rollomatic Light

Válido para los modelos: HT 130, HT 131, MS 170, MS 171, MS 180, MS181, MSA 220, MSA 200, MS 201 T, MS 194 T, MS 211

Anclajes espada: Tipo 3005

Número de dientes: 9

Referencias STIHL: 30050007409, 3005 000 7409, 3005-000-7409



STIHL
0010 940 7400 Part. B
Bar / N
Len. / 1000
Ø / 38

STIHL® **FELLOWMATIC E**
LIGHT Made in Germany

MODELO ACTUAL

Rollomatic E Mini



Rollomatic E (10)



Rollomatic E (11)



Carving



Rollomatic E Mini Light



Rollomatic E Light



Rollomatic ES Light



Rollomatic ES



Duromatic E



Rollomatic G



MODELO NUEVO

Light 01



Light 04



Light 06



Carving



Light P01



Light P04



Light X



Strong X



Strong S



Strong G



Note: The printed design of the STIHL guide bars is changed. The change is made successively. During the transition period, both printed designs will occur. Until the complete conversion to the new design, the previous designation will be retained. The part numbers will not be changed.

Colours:

- **Green:** Green marks the products which are designed to reduce the risk of kickback injury and to comply with the ANSI B175.1 kickback standard. Those products are recommended for both experienced and inexperienced chain saw users.
- **Yellow:** Products marked yellow indicate increased risk of kickback injury and are for use only by persons with extraordinary cutting needs and experience and specialized training for dealing with kickback.

Bar type and features:

Light		3-piece laminated guide bar
Light X		Lightweight solid guide bar with an aluminum core and replaceable bar nose
Strong		Solid guide bar
Carving		A high quality guide bar for carving
G		Solid guide bar with water supply (for concrete cutters)
S		Solid guide bar with carbide reinforcement at the bar tip
X		Exchangeable sprocket nose
P		Lightweight guide bar with fiberglass-reinforced polyamide
01/04/06		Number of rivets in the sprocket nose